

## BSC range for bore pile filling

## BSC 1409 D4

Concrete pressure up to 71 bar  
Output up to 97 m<sup>3</sup>/h



Note: This is a merely informative, non-binding document. Maximum theoretical values listed. Specifications are subject to change without prior notice. Photos and drawings are for illustrative purposes only. For available options, please consult the factory.

### Technical data

Dimensions		
Length	mm	6,506
Width	mm	2,197
Height	mm	2,447
Weight	kg	9,000
Concrete pump		
Output up to	m <sup>3</sup> /h	97/67*
Concrete pressure up to	bar	71/106*
Pump strokes	1/min	37
Delivery cylinder stroke	mm	1,400
Delivery cylinder diameter	mm	200
Pressure connection	m	5.5" (125)

\* concrete pump (piston side)

Hopper			
Capacity	l	600	
Max. noise level	dB	108	
Central lubrication			
Rubber collar			
Chassis			
Engine Diesel Deutz, 4 cylinders			
Engine power at	kW (HP)	150 (204)	
	rpm	2,300	
Engine emissions Stage IV / Tier 4f			
Steel crawlers, TFW-Fahrtechnik			
Max. speed	km/h	2	
Diesel tank	l	135	
Lights 2 on the hopper, 1 in front			

## Technical data

Remote control		
Radio remote control (transport and output)		
Cable remote control (output)		
Cable length	m	10
Cleaning equipment		
Water tank	l	800
Cleaning pump	l/min /bar	50 / 20
Air compressor	l/min	820
Pressured air tank	l	60
Safety platform		
Accessories		

Others
Standard coat of paint MB 1227 Yellow
Technical documents 1 paper copy, 1 CD-ROM
Tool box
Emergency button
Electric vibrator

## Optionals

Automatic central lubrication
High pressure water pump

## Transport dimensions

